

IFC MODEL	2FB6T(S)BBTN	IRB20TCSC0 (NF)	IRB20TCSCO	IRB20TSSRO	2FB10TSSRL	2SB900TCSSL
Size Range	1/4" thru 4"	1/4" thru 2"	1/4" thru 2"	1/4" thru 2"	1/4" thru 3"	1/4" thru 2"
Type	Two Piece	Unibody	Unibody	Unibody	Two-Piece	Two-Piece
MAWP	600 psig	2000 psig	2000 psig	2000 psig	1000 psig	ANSI 900 LB
Port	Full	Reduced	Reduced	Reduced	Full	Regular
Ends	NPT/CxC	NPT	NPT	NPT	NPT	NPT
Body	Brass	WCB	WCB	CF8M	CF8M	WCB
Ball, Trim	Brass	316SS	316SS	316SS	316SS	316SS
Seat	PTFE	Polycarbon	Polycarbon	RTFE	RTFE	Polycarbon
Seals	PTFE	Graphoil	Graphoil	Graphoil	PTFE	Graphoil
Operator	Lever	Oval	Oval	Oval	Locking Lever	Locking Lever
NACE MR01-75						
API 607 Fire Safe						
Anti-Static Device						
Pressure Equalization Hole in Ball						
Tapped Mounting Pad						
Other	CAN/CGA Approved	None Firesafe - Econ. Steam Valve	None	None	None	Seal Welded Body to Adapter
Catalogue Page No.	4, 5	6, 7	6, 7	6, 7	8, 9	8, 9

IFC MODEL	2SB900TSSRL	3FB10TSSRL	3SB20TCSSL	3SB20TSSRL	2FB1500TCSDL	2FB1500TSSDL
Size Range	1/4" thru 2"	1/2" thru 2"	1/2" thru 2"	1/2" thru 2"	1/4" thru 2"	1/4" thru 2"
Type	Two-Piece	Three Piece	Three Piece	Three Piece	Two Piece	Two Piece
MAWP	ANSI 900 LB.	1000 psig	2000 psig	2000 psig	ANSI 1500 Lb.	ANSI 1500 Lb.
Port	Regular	Full	Regular	Regular	Full (Note 1)	Full (Note 1)
Ends	NPT	NPT/SV	NPT/SW	NPT/SW	NPT	NPT
Body	CF8M	CF8M	WCB	CF8M	WCB	CF8M
Ball, Trim	316SS	316SS	316SS	316SS	316SS	316SS
Seat	RTFE	RTFE	Polycarbon	RTFE	Delrin	Delrin
Seals	Graphoil	PTFE	Graphoil	Graphoil	Graphoil	Graphoil
Operator	Locking Lever	Locking Lever	Locking Lever	Locking Lever	Locking Lever	Locking Lever
NACE MR01-75						
API 607 Fire Safe						
Anti-Static Device						
Pressure Equalization Hole in Ball						
Tapped Mounting Pad						
Other	Seal Welded Body to Adapter	Exposed Bolting	Non-Exposed Bolting	Non-Exposed Bolting	None	None
Catalogue Page No.	8, 9	10, 11	10, 11	10, 11	12, 13	12, 13

Note 1: Full Port sizes 1/4", 1/2", 3/4" and 1-1/2", Regular Port Sizes 1" and 2".

IFC MODEL	2FB60TC SPL	2FB60TSSPL	2FB150FC SCL	2FB150FSSRL	2FB300FC SCL	2FB300FSSRL
Size Range	1/4" thru 2"	1/4" thru 2"	1/2" thru 12"	1/2" thru 12"	1/2" thru 10"	1/2" thru 10"
Type	Two Piece	Two Piece	Split Body	Split Body	Split Body	Split Body
MAWP	6000 psig	6000 psig	ANSI 150 Lb.	ANSI 150 Lb.	ANSI 300 LB.	ANSI 300 LB.
Port	Full (Note 1)	Full (Note 1)	Full	Full	Full	Full
Ends	NPT	NPT	RF Flanged	RF Flanged	RF Flanged	RF Flanged
Body	WCB	CF8M	WCB	CF8M	WCB	CF8M
Ball, Trim	CF8M	CF8M	316SS	316SS	316SS	316SS
Seat	Peek	Peek	Polycarbon	RTFE	Polycarbon	RTFE
Seals	Graphoil	Graphoil	Graphoil	Graphoil	Graphoil	Graphoil
Operator	Locking Lever	Locking Lever	Lever/Gear	Lever/Gear	Lever/Gear	Lever/Gear
NACE MR01-75						
API 607 Fire Safe						
Anti-Static Device						
Pressure Equalization Hole in Ball						
Tapped Mounting Pad						
Other	Seal Welded Body to Adapter	Seal Welded Body to Adapter				
Catalogue Page No.	12, 13	12, 13	14, 15	14, 15	14, 15	14, 15

Note 1: Full Port sizes 1/4", 1/2", 3/4" and 1-1/2", Regular Port Sizes 1" and 2".

IFC is continuously adding to our stocking and manufacturing program. Please consult factory if valve and trim required is not shown.